



ECHOTAC Acoustic Tack Board

ECHOTAC Acoustic Tack Board is suitable for use in corporate and educational areas that receive normal abuse, need tackable surfaces and sound control.

This product can be prefabricated or built on site using our B.O.S.S. acoustic mounting system for large applications, such as tackable walls.

PHYSICAL PROPERTIES

Material	ECHOTAC Sustainable mineral fiber core Recycled content 56% <ul style="list-style-type: none"> • 37% pre-consumer • 19% post-consumer • Rapidly renewable content 1% • CHIPS - Pass • VOC - Low
LEED	MR Credit 4.1 = 1 point MR Credit 4.2 = 1 point MR Credit 6
Density	16 lb/ft ³
Fire Rating	ASTM E 84 all components are Class A
Finish	Fabric Wrapped in a Variety of Colours

BENEFITS

- Absorbs and reduces noise
- Extremely Rigid/Tackable
- Class A fire-rated (ASTM E 84)
- Prefabricated Panels or Built on Site to Suite Custom Sizes

USES AND APPLICATIONS

- Lobbies
- Public Venues
- Entertainment Facilities
- Classrooms
- Corporate Offices
- Common Areas
- Safety Boards

SIZES/COLOURS

- Up to 4'x10' Prefabricated
- Custom Sizes Available
- Fabric Wrapped in a Wide Range of Colours

TOTAL ABSORPTION

	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	NRC
1/2"	0.06	0.20	0.47	0.61	0.64	0.73	0.50
3/4"	0.08	0.30	0.53	0.65	0.81	0.87	0.55

Tested per ASTM C-423 in a type A mounting with unbacked, acoustically transparent panel fabric